


GRASS & GROUND REINFORCEMENT

PFS-GRID









Geogrid is a high quality heavy duty ground reinforcement tile and cellular paving system.



PFS Europe by

Schutboomstraat 30 5402 LL Uden, Netherlands

- **T:** +31(0)413 25 66 44 (office)
- **T:** +31(0)416 74 71 13 (factory-visits)
- **M:** +31(0)6 519 810 37
- **E:** info@pfseurope.com **I:** www.pfseurope.com

- Car parts & event parking
- Equestrian & outdoor events
- Acces roads & verges
- Road extensions and widening
- Fire & emergency routes
- Pathways & driveways

PFS-GRID

Semi or permanent ground reinforcement













FEATURES

- Unique interlocking design
- ECO friendly
- Durable yet light weight
- 10+ Life span
- Non-slip and weatherproof
- Unaffected by heat or cold
- Zero maintenance
- Prevents soil erosion
- Provides water dispersion
- Fast and simple to install
- Optimun contraction an expansion capability
- Sustainable urban drainage systems (SUDS)
- Installation guide available on request
- Soil, grass or gravel infill

TECHNICAL DATA

MATERIAL Geogrid is made from 100% recycled

polymer, frost, UV and chemical resistance

working temp. -30℃ to +50℃.

SIZE 495 mm x 495 mm x 40 mm.

WEIGHT 1.1 kg per tile / 4.4 kg per m².

WEIGHT LOADING 30 tonnes axle weight; 450 tonnes m².

PACKAGING 260 tiles per pallet. 65 m² per pallet.

Preconnected in one m² layers. Loaded pallet weight 300 kg.

INSTALLATION RATE Easy to install and can be laid at the rate of

100 m² per person per hour.